This document provides pertinent information concerning the reissuance of the VPDES Permit listed below. This permit is being processed as a Minor, Municipal permit. The discharge results from the operation of a 0.015 MGD wastewater treatment plant. This permit action consists of updating the proposed effluent limits to reflect the current Virginia Water Quality Standards (effective January 6, 2011) and updating permit language as appropriate. The effluent limitations and special conditions contained within this permit will maintain the Water Quality Standards of 9VAC25-260 et seq.

Facility Name and Mailing Aldie Wastewater Treatment Plant SIC Code: 4952 WWTP Address: P.O. Box 4000 Ashburn, VA 20146 Facility Location: 39506 John Mosby Hwy County: Loudoun Aldie, VA 20105 Facility Contact Name: Ben Shoemaker Telephone Number: (571) 291-7937 Facility Email Address: bshoemaker@loudounwater.org VA0089133 2. Permit No.: Expiration Date: December 14, 2016 Other VPDES Permits: Not Applicable (NA) Other Permits: NA E2/E3/E4 Status: NA Owner Name: Loudoun County Sanitation Authority dba Loudoun Water 3. Ben Shoemaker, Regulatory Affairs and Owner Contact / Title: Telephone Number: (571) 291-7937 Compliance Owner Email Address: bshoemaker@loudounwater.org **Application Complete Date:** June 2, 2016 Permit Drafted By: Alison Thompson Date Drafted: September 6, 2016 Draft Permit Reviewed By: Anna Westernik Date Reviewed: September 9, 2016 Public Comment Period: Start Date: End Date: 5. Receiving Waters Information: See Attachment 1 for the Flow Frequency Determination. Receiving Stream Name: Stream Code: 1aLIV Little River Drainage Area at Outfall: River Mile: 4.58 41.4 sq.mi. Potomac River Potomac River Stream Basin: Subbasin: Section: Stream Class: III VAN-A08R; PL13 Special Standards: None Waterbody ID: 0.14 MGD 7Q10 High Flow: 7Q10 Low Flow: 1.7 MGD 1Q10 Low Flow: 0.11 MGD 1Q10 High Flow: 1.2 MGD 30Q10 Low Flow: 0.30 MGD 30Q10 High Flow: 3.0 MGD Harmonic Mean Flow: 2.6 MGD 30Q5 Flow: 0.56 MGD 6. Statutory or Regulatory Basis for Special Conditions and Effluent Limitations: State Water Control Law **EPA Guidelines** Water Quality Standards X Clean Water Act X VPDES Permit Regulation Other (PES, Occoquan Policy, Dulles)

(GP – note regulation and title)

7. Licensed Operator Requirements: Class IV

X EPA NPDES Regulation

8.	Reliab	ility Class:	Clas	s I	
9.	Facilit	y / Permit Characterization:			
		Private	X	Effluent Limited	Possible Interstate Effect
		Federal	X	Water Quality Limited	Compliance Schedule
		State		Whole Effluent Toxicity Program	Interim Limits in Permit
	X	POTW		Pretreatment Program	 Interim Limits in Other Document
	X	eDMR Participant	X	Total Maximum Daily Load (TMDL)	

#### 10. Wastewater Sources and Treatment Description:

The Aldie WWTP serves the small community of Aldie with an approximate population of 178 (approximately 51 connections). There are no known industrial discharges to the wastewater plant.

The 0.015 MGD wastewater treatment plant treats the municipal wastewater utilizing a bar screen, extended aeration, clarification, disinfection with ultraviolet radiation (UV), and post aeration.

TABLE 1 OUTFALL DESCRIPTION						
Number	Discharge Sources	Treatment	Design Flow	Latitude / Longitude		
001	Domestic Wastewater	See Section 10	0.015 MGD	38° 58′ 39″ 77° 38′ 14″		
See Attachm	See Attachment 2 for (Middleburg, DEQ #206B) topographic map.					

#### 11. Sludge Treatment and Disposal Methods:

The waste activated sludge is stored in an aerated holding tank. The facility pumps and hauls the sludge to the Broad Run WRF (VA0091383) on an as needed basis.

#### 12. Other Permitted Discharges and Monitoring Stations Located Within Waterbody VAN-A08R:

TABLE 2 LOCATED WITHIN WATERBODY VAN-A08R					
ID / Permit Number	Name	Туре	Stream		
1aLIV004.78	DEQ Monitoring Stations	Ambient and Biological	Little River at Route 50 Bridge		
1aLIV001.70	DEQ Monitoring Stations	Ambient	Little River at Route 15 Bridge		

#### 13. Material Storage:

There are no materials stored onsite.

#### 14. Site Inspection:

Performed by DEQ-NRO Water Compliance staff on November 5, 2009 (Attachment 3).

#### 15. Receiving Stream Water Quality and Water Quality Standards:

#### a. Ambient Water Quality Data

This facility is located on Little River. DEQ Ambient monitoring station 1aLIV004.78 is located on Little River at Route 50, approximately 0.20 mile upstream from Outfall 001. DEQ Ambient monitoring station 1aLIV001.70 is located on Little River at Route 15, approximately 3.0 miles downstream from Outfall 001. The following is the water quality summary for this segment of Little River, as taken from the 2014 Integrated Report:

Class III, Section 9.

DEQ monitoring stations located in this segment of Little River:

- ambient water quality monitoring station 1aLIV001.70, at Route 15
- ambient water quality monitoring station 1aLIV004.78, at Route 50

Biological monitoring finds benthic macroinvertebrate impairments, resulting in an impaired classification for the aquatic life use. A benthic (sediment) TMDL for the Little River watershed has been completed and approved. The recreation and wildlife uses are considered fully supporting. The fish consumption use was not assessed.

#### b. 303(d) Listed Stream Segments and Total Maximum Daily Loads (TMDLs)

	TABLE 3. 303(D) IMPAIRMENT AND TMDL FOR THE RECEIVING STREAM								
Waterbody Name	WLA	Basis for WLA							
Little River	Aquatic Life	Benthic Macro- invertebrates	Goose Creek Watershed Benthic (Sediment) 04/26/2004	0.7 tons sediment/ year**	TSS concentration 30 mg/L 0.015 MGD				

\*This facility was assigned a total WLA of 3.5 tons/year in the Benthic TMDL for the Goose Creek and Little River watersheds. This total WLA was calculated based upon the permitted maximum average concentration for TSS (mg/L) and an assumption of the facility operating at five times the design flow. The factor of five for the design flow was used as a conservative measure to build in future growth in the watershed. Although the future growth for the watershed was determined by the design flow of each facility within in the watershed, the future growth is available for both new and expanding permits in the watershed. The actual WLA for this facility without including the future growth is 0.7 tons/year.

The remainder of this page was intentionally left blank.

	TABLE 4. INFORMATION ON DOWNSTREAM 303(D) IMPAIRMENTS AND TMDLS									
Waterbody Name	Impaired Use	Cause	Distance From Outfall	TMDL completed	WLA	Basis for WLA				
Goose Creek	Recreation	E. coli	12.3 miles	Goose Creek Bacteria TMDL 5/1/2003	4.16E+10 cfu/year fecal coliform bacteria  2.61E+10 cfu/year E. coli bacteria*	200 cfu/100 ml fecal coliform 126 cfu/100 ml <i>E. coli*</i>  0.015 MGD				
Goose Creek Reservoir	Fish Consumption	PCBs	11.3 miles	No						

<sup>\*</sup> The WLA is expressed in the Goose Creek Watershed Bacteria TMDL as cfu/year fecal coliform.

This facility discharges to the Little River within the Chesapeake Bay watershed. The receiving stream has been identified in the Chesapeake Bay TMDL; approved by the Environmental Protection Agency (EPA) on December 29, 2010. The TMDL addresses dissolved oxygen (D.O.), chlorophyll a and submerged aquatic vegetation (SAV) impairments in the main stem Chesapeake Bay and its tributaries by establishing nonpoint source load allocations (LAs) and point source wasteload allocations (WLAs) for Total Nitrogen (TN), Total Phosphorus (TP) and Total Suspended Solids (TSS) to meet applicable Virginia Water Quality Standards contained in 9VAC25-260-185.

Implementation of the Chesapeake Bay TDML is currently accomplished in accordance with the Commonwealth of Virginia's Phase I Watershed Implementation Plan (WIP); approved by EPA on December 29, 2010. The approved WIP recognizes the *General VPDES Watershed Permit Regulation for Total Nitrogen and Total Phosphorus Discharges and Nutrient Trading in the Chesapeake Bay Watershed of Virginia* (9VAC25-820 et seq.) as controlling the nutrient allocations for non-significant Chesapeake Bay dischargers. The approved WIP states that for non-significant municipal facilities, nutrient WLAs are to be consistent with Code of Virginia procedures, which set baseline WLAs at 2005 permitted design capacity nutrient load levels. In accordance with the WIP, TN and TP WLAs for non-significant facilities are considered aggregate allocations and will not be included in individual permits. The WIP also considers TSS WLAs for non-significant facilities to be aggregate allocations; however, TSS limits are to be included in individual VPDES permits in conformance with the technology-based requirements found in the Clean Water Act. Furthermore, the WIP recognizes that so long as the aggregated TSS permitted loads for all dischargers is less than the aggregated TSS load in the WIP, the individual permit will be consistent with the TMDL.

40 CFR 122.44(d)(1)(vii)(B) requires permits to be written with effluent limits necessary to meet water quality standards and to be consistent with the assumptions and requirements of applicable WLAs. This facility is classified as a non-significant Chesapeake Bay discharger and has not made application for a new or expanded discharge since 2005. It is therefore covered by rule under the 9VAC25-820 regulation. In accordance with the WIP, TN and TP load limits are not included in this individual permit, but are consistent with the TMDL because the current nutrient loads are in conformance with the facility's 2005 permitted design capacity loads. This individual permit includes weekly average TSS limits of 30 mg/L that are in conformance with technology-based requirements and, in turn, are consistent with the Chesapeake Bay TMDL.

In addition, this individual permit contains limits for ammonia, BOD<sub>5</sub> and D.O. which provide protection of instream D.O. concentrations of at least 5.0 mg/L. Furthermore, implementation of the full Chesapeake Bay WIP, including GP reductions combined with actions proposed in other source sectors, is expected to adequately address ambient conditions such that the proposed effluent limits found within this individual permit are consistent with the Chesapeake Bay TMDL and will not cause an impairment or observed violation of the standards for D.O., chlorophyll a or SAV as required by 9VAC25-260-185.

The planning statement is found in Attachment 4.

#### c. Receiving Stream Water Quality Criteria

Part IX of 9VAC25-260(360-550) designates classes and special standards applicable to defined Virginia river basins and sections. The receiving stream, Little River, is located within Section 9 of the Potomac River Basin and classified as Class III water.

At all times, Class III waters must achieve a dissolved oxygen (D.O.) of 4.0 mg/L or greater, a daily average D.O. of 5.0 mg/L or greater, a temperature that does not exceed  $32^{\circ}$  C and maintain a pH of 6.0 - 9.0 standard units (S.U.).

The Freshwater Water Quality/Wasteload Allocation Analysis located in Attachment 5 details other water quality criteria applicable to the receiving stream.

Some Water Quality Criteria are dependent on the pH, temperature and total hardness of the receiving stream and/or final effluent.

#### pH and Temperature for Ammonia Criteria

The fresh water, aquatic life Water Quality Criteria for ammonia is dependent on the instream pH and temperature. Since the effluent may have an impact on the instream values, the pH and temperature values of the effluent must also be considered when determining the ammonia criteria for the receiving stream. The 90th percentile pH and temperature values are utilized because they best represent the critical conditions of the receiving stream.

DEQ Ambient Monitoring data for watershed VAN-A08R from January 1990 through February 2011 was reviewed and the 90<sup>th</sup> percentile values were calculated. These values shall be used in Attachment 5 to determine the ammonia criteria. The 90<sup>th</sup> percentile annual pH is 8.0 S.U and temperature is 23.4°C. The 90<sup>th</sup> percentile wet season pH is 8.0 S.U. and the temperature is 12.7°C. The 10<sup>th</sup> percentile pH is 7.0 S.U.

The facility data reported on the Discharge Monitoring Reports from January 2014 through July 2016 was reviewed. There are no significant changes from the assumptions used for the last two reissuances; therefore, a pH value of 7.5 S.U. shall be carried forward for this reissuance. A default value of 15°C was used for the wet season temperature and 20°C was used for the annual temperature since the temperature data was not readily available.

#### Hardness Dependent Metals Criteria

The Water Quality Criteria for some metals are dependent on the receiving stream's hardness (expressed as mg/L calcium carbonate). There is no hardness data for this facility. Staff guidance suggests using a default hardness value of 50 mg/L CaCO $_3$  for streams east of the Blue Ridge. The hardness-dependent metals criteria in Attachment 5 are based on this default value.

DEQ Ambient Monitoring data for watershed VAN-A08R from January 1990 through February 2011 was reviewed and the average Total Hardness value was calculated to be 83.6 mg/L. This value along with the effluent default value shall be used in Attachment 5 to determine the hardness-dependent metals criteria.

#### Bacteria Criteria

The Virginia Water Quality Standards at 9VAC25-260-170A state that the following criteria shall apply to protect primary recreational uses in surface waters:

E. coli per 100 mL of water shall not exceed the following:

	Geometric Mean <sup>1</sup>
Freshwater E. coli (N/100 mL)	126

<sup>&</sup>lt;sup>1</sup>For a minimum of four weekly samples taken during any calendar month

#### d. Receiving Stream Special Standards

The State Water Control Board's Water Quality Standards, River Basin Section Tables (9VAC25-260-360, 370 and 380) designates the river basins, sections, classes and special standards for surface waters of the Commonwealth of Virginia. The receiving stream, unnamed tributary to Beaverdam Creek, is located within Section 9 of the Potomac River Basin. This section has not been designated with a special standard.

#### e. Threatened or Endangered Species

The Virginia DGIF Fish and Wildlife Information System Database was searched on June 14, 2016 for records to determine if there are threatened or endangered species in the vicinity of the discharge. The following threatened or endangered species were identified within a 2 mile radius of the discharge: Green Floater and Yellow Lance. The limits proposed in this draft permit are protective of the Virginia Water Quality Standards and protect the threatened and endangered species found near the discharge. The database search can be found in Attachment 6.

DCR, FWS, and DGIF all requested coordination on this permit. The permit was sent to DCR, FWS, and DGIF and responses were received on August 26, 2016, June 28, 2016 and July 13, 2016, respectively. The responses received from these agencies have been placed in the correspondence file for this reissuance. None objected to the reissuance based on the information provided by the permittee and DEQ.

#### 16. Antidegradation (9VAC25-260-30):

All state surface waters are provided one of three levels of antidegradation protection. For Tier 1 or existing use protection, existing uses of the water body and the water quality to protect these uses must be maintained. Tier 2 water bodies have water quality that is better than the water quality standards. Significant lowering of the water quality of Tier 2 waters is not allowed without an evaluation of the economic and social impacts. Tier 3 water bodies are exceptional waters and are so designated by regulatory amendment. The antidegradation policy prohibits new or expanded discharges into exceptional waters.

Historically, the Little River at the point of discharge has been considered Tier 1. Limits for the discharge were established by determining wasteload allocations which result in attaining and/or maintaining all water quality criteria which apply to the receiving stream, including narrative criteria. These wasteload allocations will provide for the protection and maintenance of all existing uses. This Tier 1 determination shall be carried forward with this reissuance.

The proposed permit limits have been established by determining wasteload allocations which will result in attaining and/or maintaining all water quality criteria which apply to the receiving stream, including narrative criteria. These wasteload allocations will provide for the protection and maintenance of all existing uses.

#### 17. Effluent Screening, Wasteload Allocation, and Effluent Limitation Development:

To determine water quality-based effluent limitations for a discharge, the suitability of data must first be determined. Data is suitable for analysis if one or more representative data points are equal to or above the quantification level ("QL") and the data represent the exact pollutant being evaluated.

Next, the appropriate Water Quality Standards are determined for the pollutants in the effluent. Then, the Wasteload Allocations (WLA) are calculated. The WLA values are then compared with available effluent data to determine the need for effluent limitations. Effluent limitations are needed if the 97th percentile of the daily effluent concentration values is greater than the acute wasteload allocation or if the 97th percentile of the four-day average effluent concentration values is greater than the chronic wasteload allocation. Effluent limitations are then calculated on the most limiting WLA, the required sampling frequency, and statistical characteristics of the effluent data.

#### a. Effluent Screening

Effluent data obtained from the permit application and the Discharge Monitoring Reports (DMRs) submitted during the last permitting term has been reviewed and determined to be suitable for evaluation. The following pollutants require a wasteload allocation analysis: Ammonia as N.

#### b. Mixing Zones and Wasteload Allocations (WLAs)

Wasteload allocations (WLAs) are calculated for those parameters in the effluent with the reasonable potential to cause an exceedance of water quality criteria. The basic calculation for establishing a WLA is the steady state complete mix equation:

 $\frac{\text{Co}\left[\text{Qe}+(\text{f})(\text{Qs})\right]-\left[(\text{Cs})(\text{f})(\text{Qs})\right]}{\text{Qe}}$ WLA Where: WLA = Wasteload allocation Co = In-stream water quality criteria Qe = Design flow f = Decimal fraction of critical flow from mixing evaluation Qs = Critical receiving stream flow (1Q10 for acute aquatic life criteria; 7Q10 for chronic aquatic life criteria; 30Q10 for ammonia criteria; harmonic mean for carcinogen-human health criteria; and 30Q5 for non-carcinogen human health criteria) Cs = Mean background concentration of parameter in the receiving stream.

The Water Quality Standards contain two distinct mixing zone requirements. The first requirement is general in nature and requires the "use of mixing zone concepts in evaluating permit limits for acute and chronic standards in 9VAC25-260-140.B". The second requirement is specific and establishes special restrictions for regulatory mixing zones "established by the Board".

The Department of Environmental Quality uses a simplified mixing model to estimate the amount of mixing of a discharge with the receiving stream within specified acute and chronic exposure periods. The simplified model contains the following assumptions and approximations:

- The effluent enters the stream from the bank, either via a pipe, channel or ditch.
- The effluent velocity isn't significantly greater (no more than 1 2 ft/sec greater) than the stream velocity.
- The receiving stream is much wider than its depth (width at least ten times the depth).
- Diffusive mixing in the longitudinal direction (lengthwise) is insignificant compared with advective transport (flow).
- Complete vertical mixing occurs instantaneously at the discharge point. This is assumed since the stream depth is
  much smaller than the stream width.
- Lateral mixing (across the width) is a linear function of distance downstream.
- The effluent is neutrally buoyant (e.g. the effluent discharge temperature and salinity are not significantly different from the stream's ambient temperature and salinity).
- Complete mix is determined as the point downstream where the variation in concentration is 20% or less across the width and depth of the stream.
- The velocity of passing and drifting organisms is assumed equal to the stream velocity.

If it is suitably demonstrated that a reasonable potential for lethality or chronic impacts within the physical mixing area doesn't exist, then the basic complete mix equation, with 100% of the applicable stream flow, is appropriate. If the mixing analysis determines there is a potential for lethality or chronic impacts within the physical mixing area, then the proportion of stream flow that has mixed with the effluent over the allowed exposure time is used in the basic complete mix equation. As such, the wasteload allocation equation is modified to account for the decimal fraction of critical flow (f).

Staff derived wasteload allocations where parameters are reasonably expected to be present in an effluent (e.g., total residual chlorine where chlorine is used as a means of disinfection) and where effluent data indicate the pollutant is present in the discharge above quantifiable levels. With regard to the Outfall 001 discharge, ammonia as N is likely present since this is a WWTP treating sewage. As such, Attachment 5 details the mixing analysis results and WLA derivations for these pollutants.

#### c. <u>Effluent Limitations</u>, Outfall 001 – Toxic Pollutants

9VAC25-31-220.D. requires limits be imposed where a discharge has a reasonable potential to cause or contribute to an instream excursion of water quality criteria. Those parameters with WLAs that are near effluent concentrations are evaluated for limits.

The VPDES Permit Regulation at 9VAC25-31-230.D requires that monthly and weekly average limitations be imposed for continuous discharges from POTWs and monthly average and daily maximum limitations be imposed for all other continuous non-POTW discharges.

#### 1) Ammonia as N

Staff reevaluated the need for ammonia as N limitations. Staff used the values presented in Section 15 of the Fact Sheet to determine the ammonia water quality criteria and wasteload allocations (WLAs). DEQ guidance suggests using a sole data point of 9.0 mg/L for discharges containing domestic sewage to ensure the evaluation adequately addresses the potential for ammonia to be present in the discharge containing domestic sewage. The current evaluation (Attachment 7) demonstrates that no limits are necessary for this discharge.

The Environmental Protection Agency (EPA) finalized new, more stringent ammonia criteria in August 2013; possibly resulting in significant reductions in ammonia effluent limitations. It is staff's professional judgment that the incorporation of those criteria into the Virginia Water Quality Standards is forthcoming. This and many other facilities may be required to comply with these new criteria during their next respective permit terms. The ammonia criteria will be revisited during the next reissuance.

#### d. Effluent Limitations and Monitoring, Outfall 001 - Conventional and Non-Conventional Pollutants

No changes to dissolved oxygen (D.O.), biochemical oxygen demand-5 day (BOD<sub>5</sub>), total suspended solids (TSS), *E. coli*, and pH limitations are proposed.

The BOD<sub>5</sub> and TSS limitations are based on the Federal Secondary Treatment Standards at 40 CFR Part 133 and the VPDES Permit Regulation at 9VAC25-31-30.

pH and dissolved oxygen limitations are set at the water quality criteria.

E. coli limitations are in accordance with the Water Quality Standards 9VAC25-260-170.

#### e. <u>Effluent Annual Average Limitations and Monitoring, Outfall 001 – Nutrients</u>

As discussed in Section 15, significant portions of the Chesapeake Bay and its tributaries are listed as impaired with nutrient enrichment cited as one of the primary causes. Virginia has committed to protecting and restoring the Bay and its tributaries. Only concentration limits are now found in the individual VPDES permit when the facility installs nutrient removal technology. The basis for the concentration limits is 9VAC25-40-Regulation for Nutrient Enriched Waters and Dischargers within the Chesapeake Bay Watershed which requires new or expanding discharges with design flows of  $\geq 0.04$  MGD to treat for TN and TP to either BNR (Biological Nutrient Removal) levels (TN = 8 mg/L; TP = 1.0 mg/L) or SOA (State of the Art) levels (TN = 3.0 mg/L and TP = 0.3 mg/L).

Annual monitoring for Nitrates + Nitrites, Total Kjeldahl Nitrogen, Total Nitrogen, and Total Phosphorus are included in this permit. The monitoring is needed to protect the Chesapeake Bay Water Quality Standards and verify assumptions made while developing the Watershed Implementation Plan (WIP) for the Chesapeake Bay TMDL.

#### f. Effluent Limitations and Monitoring Summary

The effluent limitations are presented in Section 19. Limits were established for Biochemical Oxygen Demand-5 day  $(BOD_5)$ , Total Suspended Solids (TSS), pH, Dissolved Oxygen (D.O.), and *E. coli*. Monitoring is included for Flow, Total Kjeldahl Nitrogen (TKN), Nitrates+Nitrites, Influent BOD<sub>5</sub>, Influent TSS, Total Nitrogen, and Total Phosphorus.

The mass loading (kg/d) for monthly and weekly averages were calculated by multiplying the concentration values (mg/L), with the flow values (in MGD) and then a conversion factor of 3.785.

Sample Type and Frequency are in accordance with the recommendations in the VPDES Permit Manual.

The VPDES Permit Regulation at 9VAC25-31-30 and 40 CFR Part 133 require that the facility achieve at least 85% removal for BOD and TSS (or 65% for equivalent to secondary). This permit requires influent BOD<sub>5</sub> and TSS monitoring on an annual basis to demonstrate 85% removal.

#### 18. Antibacksliding:

All limits in this permit are at least as stringent as those previously established. Backsliding does not apply to this reissuance.

#### 19. Effluent Limitations/Monitoring Requirements:

Design flow is 0.015 MGD.

Effective Dates: During the period beginning with the permit's effective date and lasting until the expiration date.

PARAMETER	BASIS FOR	DISCHARGE LIMITATIONS				MONITORING REQUIREMENTS	
	LIMITS	Monthly Average	Weekly Average	Minimum	Maximum	Frequency	Sample Type
Flow (MGD)	NA	NL	NA	NA	NL	1/D	Estimate
pН	1	NA	NA	6.0 S.U.	9.0 S.U.	1/D	Grab
$BOD_5$	1,3	30 mg/L 1.7 kg/day	45 mg/L 2.6 kg/day	NA	NA	1/ <b>M</b>	Grab
Total Suspended Solids (TSS)	2,3	30 mg/L 1.7 kg/day	45 mg/L 2.6 kg/day	NA	NA	1/ <b>M</b>	Grab
Dissolved Oxygen (DO)	1	NA	NA	5.0 mg/L	NA	1/D	Grab
E. coli (Geometric Mean) a.	1,6,7	126 n/100mL	NA	NA	NA	1/W	Grab
Total Kjeldahl Nitrogen (TKN)	4,5	NL mg/L	NA	NA	NA	1/YR	Grab
Nitrate+Nitrite, as N	4,5	NL mg/L	NA	NA	NA	1/YR	Grab
Total Nitrogen b.	4,5	NL mg/L	NA	NA	NA	1/YR	Calculated
Total Phosphorus	4,5	NL mg/L	NA	NA	NA	1/YR	Grab
Influent BOD <sub>5</sub> c.	3	NL mg/L	NA	NA	NA	1/YR	Grab
Influent TSS c.	3	NL mg/L	NA	NA	NA	1/YR	Grab

The basis for the limitations codes are:

1.	Water Quality Standards	MGD = Million gallons per day.	1/D =	Once every day.
2.	Professional Judgment	NA = Not applicable.	1/W =	Once per week.
3.	Federal Effluent Guidelines 40 CFR Part 133	NL = No limit; monitor and report.	1/M =	Once every month.
4.	GM 14-2011	S.U. = Standard units.	1/YR =	Once every calendar year.

- 5. Chesapeake Bay TMDL/WP
- 6. Goose Creek Bacteria TMDL
- 7. DEQ Disinfection Guidance

Grab = An individual sample collected over a period of time not to exceed 15 minutes.

Estimate = Reported flow is to be based on the technical evaluation of the sources contributing to the discharge.

- a. Samples shall be collected between 10:00 a.m. and 4:00 p.m.
- $b. \ \, Total \,\, Nitrogen = Sum \,\, of \,\, TKN \,\, plus \,\, Nitrate + Nitrite.$
- c. At least 85% removal for BOD and TSS shall be attained for this effluent.

#### 20. Other Permit Requirements:

a. Part I.B. of the Permit Contains Quantification Levels and Compliance Reporting Instructions.

9VAC25-31-190.L.4.c. requires an arithmetic mean for measurement averaging and 9VAC25-31-220.D requires limits be imposed where a discharge has a reasonable potential to cause or contribute to an instream excursion of water quality criteria. Specific analytical methodologies for toxics are listed in this permit section as well as quantification levels (QLs) necessary to demonstrate compliance with applicable permit limitations or for use in future evaluations to determine if the pollutant has reasonable potential to cause or contribute to a violation. Required averaging methodologies are also specified.

#### 21. Other Special Conditions:

- a. <u>95% Capacity Reopener</u>. The VPDES Permit Regulation at 9VAC25-31-200.B.4 requires all POTWs and PVOTWs develop and submit a plan of action to DEQ when the monthly average influent flow to their sewage treatment plant reaches 95% or more of the design capacity authorized in the permit for each month of any three consecutive month period. This facility is a POTW.
- b. <u>Indirect Dischargers</u>. Required by VPDES Permit Regulation, 9VAC25-31-200.B.1 and B.2 for POTWs and PVOTWs that receive waste from someone other than the owner of the treatment works.
- c. O&M Manual Requirement. Required by Code of Virginia §62.1-44.19; Sewage Collection and Treatment Regulations, 9VAC25-790; VPDES Permit Regulation, 9VAC25-31-190.E. The permittee shall maintain a current Operations and Maintenance (O&M) Manual. The permittee shall operate the treatment works in accordance with the O&M Manual and shall make the O&M Manual available to Department personnel for review upon request. Any changes in the practices and procedures followed by the permittee shall be documented in the O&M Manual within 90 days of the effective date of the changes. Non-compliance with the O&M Manual shall be deemed a violation of the permit.
- d. <u>CTC, CTO Requirement</u>. The Code of Virginia § 62.1-44.19; Sewage Collection and Treatment Regulations, 9VAC25-790 requires that all treatment works treating wastewater obtain a Certificate to Construct (CTC) prior to commencing construction and to obtain a Certificate to Operate (CTO) prior to commencing operation of the treatment works.
- e. <u>Licensed Operator Requirement</u>. The Code of Virginia at §54.1-2300 et seq. and the VPDES Permit Regulation at 9VAC25-31-200.C., and by the Board for Waterworks and Wastewater Works Operators and Onsite Sewage System Professionals Regulations (18VAC160-20-10 et seq.) requires licensure of operators. This facility requires a Class IV operator.
- f. Reliability Class. The Sewage Collection and Treatment Regulations at 9VAC25-790 require sewage treatment works to achieve a certain level of reliability in order to protect water quality and public health consequences in the event of component or system failure. Reliability means a measure of the ability of the treatment works to perform its designated function without failure or interruption of service. The facility is required to meet a reliability Class of I.
- g. Water Quality Criteria Reopener. The VPDES Permit Regulation at 9VAC25-31-220.D requires establishment of effluent limitations to ensure attainment/maintenance of receiving stream water quality criteria. Should effluent monitoring indicate the need for any water quality-based limitations, this permit may be modified or alternatively revoked and reissued to incorporate appropriate limitations.
- h. <u>Sludge Reopener</u>. The VPDES Permit Regulation at 9VAC25-31-220.C requires all permits issued to treatment works treating domestic sewage (including sludge-only facilities) include a reopener clause allowing incorporation of any applicable standard for sewage sludge use or disposal promulgated under Section 405(d) of the CWA. The facility includes a sewage treatment works.
- Sludge Use and Disposal. The VPDES Permit Regulation at 9VAC25-31-100.P; 220.B.2, and 420 through 720 and 40 CFR
  Part 503 require all treatment works treating domestic sewage to submit information on their sludge use and disposal
  practices and to meet specified standards for sludge use and disposal. The facility includes a treatment works treating
  domestic sewage.
- j. <u>Nutrient Reopener</u>. 9VAC25-40-70.A. authorizes DEQ to include technology-based annual concentration limits in the permits of facilities that have installed nutrient control equipment, whether by new construction, expansion or upgrade. 9VAC25-31-390.A. authorizes DEQ to modify VPDES permits to promulgate amended water quality standards.

k. <u>Total Maximum Daily Load (TMDL) Reopener</u>. Section 303(d) of the Clean Water Act requires that Total Maximum Daily Loads (TMDLs) be developed for streams listed as impaired. This special condition is to allow the permit to be reopened if necessary to bring it into compliance with any applicable TMDL approved for the receiving stream.

#### 22. Permit Section Part II.

Required by VPDES Regulation 9VAC25-31-190, Part II of the permit contains standard conditions that appear in all VPDES Permits. In general, these standard conditions address the responsibilities of the permittee, reporting requirements, testing procedures and records retention.

#### 23. Changes to the Permit from the Previously Issued Permit:

- a. Special Conditions:
  - No changes to the special conditions are proposed.
- b. Monitoring and Effluent Limitations:

Annual monitoring for Total Nitrogen, Total Phosphorus, Nitrate+Nitrite, and Total Kjeldahl Nitrogen were added to the effluent monitoring.

#### 24. Variances/Alternate Limits or Conditions:

Not applicable.

#### 25. Public Notice Information:

First Public Notice Date: Second Public Notice Date:

Public Notice Information is required by 9VAC25-31-280 B. All pertinent information is on file and may be inspected and copied by contacting the: DEQ Northern Regional Office; 13901 Crown Court; Woodbridge, VA 22193; Telephone No. 703-583-3834, alison.thompson@deq.virginia.gov. See Attachment 8 for a copy of the public notice document.

Persons may comment in writing or by email to the DEQ on the proposed permit action, and may request a public hearing, during the comment period. Comments shall include the name, address and telephone number of the writer and of all persons represented by the commenter/requester, and shall contain a complete, concise statement of the factual basis for comments. Only those comments received within this period will be considered. The DEQ may decide to hold a public hearing, including another comment period, if public response is significant and there are substantial, disputed issues relevant to the permit. Requests for public hearings shall state 1) the reason why a hearing is requested; 2) a brief, informal statement regarding the nature and extent of the interest of the requester or of those represented by the requester, including how and to what extent such interest would be directly and adversely affected by the permit; and 3) specific references, where possible, to terms and conditions of the permit with suggested revisions. Following the comment period, the Board will make a determination regarding the proposed permit action. This determination will become effective, unless the DEQ grants a public hearing. Due notice of any public hearing will be given. The public may request an electronic copy of the draft permit and fact sheet or review the draft permit and application at the DEQ Northern Regional Office by appointment.

#### 26. Additional Comments:

Previous Board Action(s):	There have been no recent board actions.
Staff Comments:	No comments.
State/Federal Agency Comments:	No comments.
Public Comments:	

Owner Comments:

#### Attachments to the Fact Sheet for VA0089133 Aldie WWTP

Attachment 1	Flow Frequency Determination
Attachment 2	Topographic Map
Attachment 3	Facility Inspection from September 17, 2009
Attachment 4	Planning Statement
Attachment 5	Water Quality Criteria and Wasteload Allocation Determinations
Attachment 6	DGIF Database Search Results
Attachment 7	Statistical Evaluation for the Effluent Ammonia Limitations
Attachment 8	Public Notice

# Attachment 1

#### September 6, 2016 MEMORANDUM

TO:

VPDES Reissuance File VA0089133

FROM:

Alison Thompson

SUBJECT:

Flow Frequency Determination of VPDES Permit No. VA0089133

Aldie WWTP

#### COPIES:

The reissuance of the VPDES permit for the Aldie WWTP requires an updated Flow Frequency determination in order to establish appropriate wasteload allocations for permit limit determination. The last determination was done in April 2000. There is a gaging station on Goose Creek near Leesburg, Virginia. The gaging station (#01644000) has a drainage area of 332 sq. mi. The drainage area at the outfall is approximately 41.4 sq.mi. The flows for the outfall location shall be determined using values at the Goose Creek gaging station at Leesburg, Virginia, and adjusting them by proportional drainage areas.

#### Goose Creek near Leesburg, VA (#01644000)


Drainage area	=	332 sq. mi.
1Q10		1.4 cfs
7Q10	=	1.8 cfs
30Q5	=	6.9 cfs
30Q10	=	3.7 cfs
High flow 30Q10	=	38 cfs
High flow 1Q10	=	15 cfs
High flow 7Q10	=	21 cfs
HM	=	33 cfs

#### Little River at the discharge point for Outfall 001

Drainage area	=	41.4 sq. mi.	
1Q10	=	0.17 cfs	0.11 MGD
7Q10	=	0.22 cfs	0.14 MGD
30Q5	=	0.86 cfs	0.56 MGD
30Q10	=	0.46 cfs	0.30 MGD
High flow 30Q	10 =	4.7 cfs	3.0 MGD
High flow 1Q10	) =	1.87 cfs	1.2 MGD
High flow 7Q10	) =	2.6 cfs	1.7 MGD
HM	=	4.1 cfs	2.6 MGD

The high flow months are December - May

# Attachment 2



# Attachment 3



### COMMONWEALTH of VIRGINIA

## DEPARTMENT OF ENVIRONMENTAL QUALITY NORTHERN REGIONAL OFFICE

L. Preston Bryant, Jr. Secretary of Natural Resources 13901 Crown Court, Woodbridge, Virginia 22193 (703) 583-3800 Fax (703) 583-3821 www.deq.virginia.gov

David K. Paylor Director

Thomas A. Faha Regional Director

October 2, 2009

Mr. Todd Danielson Manager of Community Systems Loudoun Water P.O. Box 4000 Ashburn, VA 20146

Re: Aldie WWTP - permit #VA0089133

Dear Owner:

Enclosed are copies of the technical and laboratory inspection reports generated from observations made while performing a Facility Technical Inspection at the Village of Aldie Sewage Treatment Plant (STP) on September 17, 2009. The compliance staff would like to thank Les Morefield and Allen Clemens for their time and assistance during the inspection.

Summaries for both the technical and laboratory inspections are enclosed. The facility had Deficiencies for the laboratory inspection. Please note the requirements and recommendations addressed in the technical summary, particularly in regard to the UV intiensity meters. Please submit in writing a progress report to this office by **November 5, 2009** for the items addressed. Your response may be sent either via the US Postal Service or electronically, via E-mail. If you choose to send your response electronically, we recommend sending it as an <u>Acrobat PDF or in a Word-compatible</u>, write-protected format. Additional inspections may be conducted to confirm that the facility is in compliance with permit requirements.

If you have any questions or comments concerning this report, please feel free to contact me at the Northern Regional Office (NRO) at (703) 583-3882 or by E-mail at Sharon.Allen@deq.virginia.gov.

Sincerely,

Sharon Allen

Environmental Specialist II Water Compliance Inspector

cc:

Permits / DMR File

anon Allow

Electronic copy sent:

Compliance Manager, Compliance Auditor – DEQ Les Morefield – Community Systems Supervisor, Loudoun Water

# DEQ WASTEWATER FACILITY INSPECTION REPORT PREFACE

				TELL	UE -				
VPDES/State Cert	VPDES/State Certification No.			ate	Amendment D	ate	Expiration Date		
VA0089	L33	July 2	8, 200	6			July 27, 2011		011
Fac	cility Name				Address		Telephone Number		umber
Aldie Wastewa	ater Treatmer	nt Plant	39506 John Mosby Highway				571-291-7700		
				Al	die, VA 20105				
Ow	ner Name				Address		Telep	hone N	umber
Loud	loun Water			P.O. Box 4000				-291-7	700
				Ash	burn, VA 20146				
	nsible Official				Title		Telep	hone N	umber
Todo	l Danielson		Mana	ager o	f Community Sys	tems	571	- 291-7	7835
Respon	sible Operator		C	perato	or Cert. Class/numb	er	Telep	hone N	umber
Dav	id Farrell		Class VI; 1912 000198				571	-291-7	700
YPE OF FACILITY:									
	DOMESTI	C				INDUST	TRIAL		
Federal	Major			Major			Prima	ry	
Non-federal X				Х	Minor			Second	ary
NFLUENT CHARACTI	ERISTICS:				DESIGN:			_a_ran_aan_ar_u( a	
		Flow			.015 MGD	9.			
		Population Se	erved		~ 100				
		Connections Se	erved 37						
		BOD <sub>5</sub>	260						
		TSS		110					
FFLUENT LIMITS: SI	PECIFY UNITS								
Parameter	Min.	Avg.	Ma	ax.	Parameter	Min.	/	Avg.	Max.
pH	6.0		9.	0	DO	5.0			
BOD5		30	4.	5	TSS			30	45
E. coli n/cml		126							
		Receiving Stre	eam		Little River				
Basin				Potomac River					
	Di	scharge Point	(LAT) 38° 58′ 39″			39"			
				ONG) 77° 38′ 14″			100		

# REV 5/00 DEQ WASTEWATER FACILITY INSPECTION REPORT PART 1

Inspection	date:	Septen	nber17, 20	09		Date For	m Completed	: Octobe	r 2, 2009	
Inspection	by:	Sharon	Alien			agency:		DEQ NR	k <b>o</b>	
Time spent	~ 6 u 4	20 Hrs				Annound	ed:	No		
Reviewed I	ру:	Q 2. 2	sc.	10/2/09				Schedule	ed: <b>Yes</b>	
	Present at inspection: Les Morefield, Allen Clemens – Loudoun Water									
TYPE OF F	ACILITY:	Domestic				Industr	ial			
[ ] Federa [ <b>X</b> ] Nonfed		[ ] Major [ <b>X</b> ] Minor				[ ] Maj [ ] Min		Primary Secondary		
Type of ins	Type of inspection:									
[X] Routine [ ] Compliance/Assistance/Complaint [ ] Reinspection						Date of Agency:	last inspectior		9/13/06 DEQ NRO	
Population	Population served: approx. 104 Connections served: approx. 37									
Last month	1		November			1				
BOD5	260	mg/L	TSS	110	mg/L.	l				
Last month			August 20	09: 7.5	0.11	DO.	7.4	ma/1		
Flow:	.0023	MGD	pH:		s.u.	DO E seli	7.4	mg/L		
Note: One	< QL e E coli san	mg/L pie analy:		9.1 ust had a re		E. coli 1600 n/cm	>12 i; two other	n/cml   r samples	were	
collected numbers >sign wa	for this mo was 12 n/o s included	onth, both cml. Howe to indicate	of which h ver, since of that a qu	ad results one sample antitative r	if < 1 n/cn result exc number wa	nl. The geo ceeded the	metric mea	n of these antitative		
Quarter av Flow:	0.0031		pH:	August 20 7.3	S.U.	DO	7.2	mg/L		
BOD <sub>5</sub>	1.7	mg/L	TSS	8.9	mg/L	E. coli	>6.5	n/cml		
	IFIED IN PR been any ne		ion?	]	] Updated		changes			
If yes, wer	re plans and	specificatio	ns approved	l? [	] Yes		[ ] No		[X] NA	
DEQ appro	oval date:	NA								

#### (A) PLANT OPERATION AND MAINTENANCE

1.	Class and number of licensed operators:	I	п	ш	IV X Traine	<del>e</del>
2.	Hours per day plant is manned:	2-3 h	rs per d	lay		
3.	Describe adequacy of staffing.		[ ]G	ood	[X] Average	[ ] Poor
4.	Does the plant have an established program for	trainin	g person	inel?	[X] Yes	[ ] No
5.	Describe the adequacy of the training program.		[ ]G	ood	[X] Average	[ ] Poor
6.	Are preventive maintenance tasks scheduled?		[ <b>X</b> ]Ye	s	[ ] No	
7.	Describe the adequacy of maintenance.		[ <b>X</b> ] G	bood	[ ] Average	[ ] Poor*
8.	Does the plant experience any organic/hydraulic If yes, identify cause and impact on plant:					
9.	Any bypassing since last inspection?		[ ] Y	es	[X] No	
10.	Is the standby electric generator operational?		[ ] Y	es	[ ] No*	[ <b>X</b> ] NA
11.	Is the STP alarm system operational?		[ ] Y	es	[ ] No*	[ <b>X</b> ] NA
12.	How often is the standby generator exercised? Power Transfer Switch? Alarm System?		NA NA NA			
13.	When was the cross connection control device is	ast test	ed on th	e potable	water service?	5/21/09
14.	Is sludge being disposed in accordance with the	appro	ved slude [ <b>X</b> ] Ye		al plan? [ ] No	[ ] NA
15.	Is septage received by the facility? Is septage loading controlled? Are records maintained?		[ ] Y	es es es	[ <b>X</b> ] No [ ] No [ ] No	[ <b>X</b> ] NA [ <b>X</b> ] NA
16.	Overall appearance of facility:		[ <b>X</b> ] Go	ood	[ ] Average	[ ] Poor

Comments:

14. The Sludge Management Plant (SMP) may have to be updated if sludge is now being hauled to Broad Run WRF instead of the Broad Run Interceptor.

**VPDES NO. VA0089133** 

#### **(B) PLANT RECORDS**

1.	Which of the following records does the plant m	aintain?						
	Operational Logs for each unit process Instrument maintenance and calibration Mechanical equipment maintenance Industrial waste contribution (Municipal Facilities)	[X] Yes [X] Yes [X] Yes [ ] Yes		[	] No ] No ] No ] No	[ ] NA [ ] NA [ ] NA [X] NA		
2.	What does the operational log contain?							
	[X] Visual observations [X] Laboratory results [ ] Control calculations	[X] Flow measu [X] Process adj [ ] Other (spec	ustments					
	Comments:							
3.	. What do the mechanical equipment records contain?							
	<ul><li>[X] As built plans and specs</li><li>[X] Manufacturers instructions</li><li>[X] Lubrication schedules</li></ul>	[ ] Spare parts [ <b>X</b> ] Equipment/ [ ] Other (spec	parts suppliers					
	Comments:							
4.	What do the industrial waste contribution record (Municipal Only)	ds contain?	NA					
	[ ] Waste characteristics [ ] Impact on plant	[ ] Locations a		pes	i			
	Comments:							
5.	Which of the following records are kept at the p	lant and availabl	e to personnel?					
	[X] Equipment maintenance records [ ] Industrial contributor records [X] Sampling and testing records	[X] Operational [X] Instrument						
6.	Records not normally available to plant personne	el and their locat	ion:					
7.	Were the records reviewed during the inspection	n?	[X] Yes	[	] No			
8.	Are the records adequate and the O & M Manua	l current?	[ ] Yes	[	] No See co	mments		
9.	Are the records maintained for the required 3-ye	ear time period?	[X] Yes	Į	] No			
C	man anta i							

Comments:

8. Records on site at the plant were acceptable.

The O&M Manual on file at the DEQ's Northern Regional Office is dated March 1997. A letter stating that the O&M manual was accurate was received by the DEQ on September 5, 2009. However, staff should confirm that the O&M manual on site is up to date; in particular, The laboratory section (Section7) must reflect the current permit requirements (e.g.- E. coli rather than fecal coliform) and include the make and model of DO and pH meters and SOPs currently in use.

		,	VPDES NO. V	A0089133	3
(C	) SA	MPLING			
	1.	Do sampling locations appear to be capable of providing representative samples?	[X] Yes	[ ] No*	
	2.	Do sample types correspond to those required by the VPDES permit?	[X] Yes	[ ] No*	
	3.	Do sampling frequencies correspond to those required by the VPDES permit?	[X] Yes	[ ] No*	
	4.	Are composite samples collected in proportion to flow?	[ ] Yes	[ ] No*	[ <b>X</b> ] NA
	5.	Are composite samples refrigerated during collection?	[ ] Yes	[ ] No*	[ <b>X</b> ] NA
	6.	Does plant maintain required records of sampling?	[X] Yes	[ ] No*	
	7.	Does plant run operational control tests?	[X] Yes	[ ] No	
		Comments:			
	(D	) TESTING			
	1.	Who performs the testing? [X] Plant [X] Central Lab	[ ] Commerc	ial Lab	
		Name: Plant- DO, pH Raspberry Falls STP lab— E. coli Broad Run WRF lab — BOD <sub>5</sub> , TSS			
	If	plant performs any testing, complete 2-4.			
	2.	What method is used for chlorine analysis? NA- plant has	UV disinfect	ion	
	3.	Does plant appear to have sufficient equipment to perform required tests?	[X] Yes	[ ] No*	:
	4.	Does testing equipment appear to be clean and/or operable?	[X] Yes	[ ] No*	:
		Comments:			
	(E)	FOR INDUSTRIAL FACILITIES WITH TECHNOLOGY BASED LIMITS ONLY			
	1.	Is the production process as described in the permit application? (If no, describe of [ ] Yes [ ] No [X] NA	changes in co	mments)	

2. Do products and production rates correspond as provided in the permit application? (If no, list differences)

[X] NA

[ ]No

3. Has the State been notified of the changes and their impact on plant effluent? Date: [ ] Yes [ ] No\* [X] NA

Comments:

[ ]Yes

Proble	ms identified at last inspection:	Corrected	Not Corrected				
1.	At the time of inspection a tree had fallen, blocking the cleared access path obtained through the woods.	n to the outfall; [X]	access was				
2.	2. The path from the fallen tree to the outfall is becoming overgrown with grass. Mr. Bell noted that the tree was scheduled to be removed and the grass beyond the tree would then be mowed.						
		[X]	[ ]				
***							

#### **SUMMARY 2009**

#### Comments:

- $\circ$  The LCD display for the Intensity Meter on the UV system was not functioning a the time of this inspection; the display was flashing 0.0  $\mu$ Ws/cm2. Plant staff have investigated the cause of the malfunction and determined that the sensor was bad and are in the process of ordering a replacement.
- The channel from Outfall 001 to the receiving stream has silted in and become grassy over the last several years. Loudoun Water staff is working on digging out the channel and restoring it to its original design.

#### Recommendations for action:

- Section 7 of the O&M Manual is out of date. The section should be revised to reflect current laboratory equipment, procedures, and quality control in use at this facility.
- o The sludge disposal plan should be reviewed and updated if necessary.

#### **UNIT PROCESS: Activated Sludge Aeration**

1.	Number of units:	1	In oper	ration:	1				
2.	Mode of operation:	Extended aer	ation						
3.	Proper flow distribution bet	ween units:	[ ] Yes	[ ] No*	[ <b>X</b> ] NA				
4.	Foam control operational:		[X] Yes	[ ] No*	[ ] NA				
5.	Scum control operational:		[X] Yes	[ ] No*	[ ] NA				
6.	Evidence of following proble a. dead spots b. excessive foam c. poor aeration d. excessive aeration e. excessive scum f. aeration equipment ma g. other (identify in comm	lfunction	[ ] Yes* [ ] Yes* [ ] Yes* [ ] Yes* [ ] Yes* [ ] Yes* [ ] Yes*	[X] No [X] No [X] No [X] No [X] No [X] No [X] No					
7.	MLSS: DO: SDI/SVI: Color: Odor:	(as available): July 2 7.0 s.u. 4680 mg/L 5.1 mg/L 85 Dark Brown earthy 520 mł/L @ 30 mi							
8.	Return/waste sludge: a. Return Rate: <b>not mea</b> : b. Waste Rate: <b>not meas</b> c. Frequency of Wasting:	ured	on process con	trol tests; gen	erally a couple	of minutes per			
9.	Aeration system control:	[X] Time Clock	[ ] Manual	[ ] Continuou	s [ ] Other (exp	lain)			
10.	Effluent control devices wor	king properly (oxidat	tion ditches):	[ ] Yes	[ ] No*	[X] NA			
11.	General condition:	[X] Good	[ ] Fair	[ ] Poor					
	omments:  One blower run per week, alternated manually								

- o Each house/building connected has a grinder pump to chop up large items prior to delivery to STP. Influent pipe goes directly into the aeration basin- end usually under water. Have to pump the tank down in order to uncover and collect the annual TSS/BOD5 influent sample.
- o Flow from each grinder pump is intermittent. Loudoun Water is investigating the option of adding treatment in the collection system to help prevent water from turning septic before it is delivered to the STP.
- o The RAS line broke in June 2007, resulting in a spill of clarifier solids to the ground around the plant. The broken coupling was repaired and the area was properly cleaned up; the spill did not affect waters of the State. There have not been any problems with the line since.

#### **UNIT PROCESS: Sedimentation**

		I	] Primary	[X] Secondary	[ ]	] Tertiary				
1.	Number of units:	1			In	operation:	1			
2.	Proper flow distribution between	ıu ı	nits:		[ ]	] Yes	E	] No*	[ <b>X</b> ]	NA
3.	Signs of short circuiting and/or	ove	rloads:		[ ]	] Yes	[ <b>X</b>	] No		
4.	Effluent weirs level: Clean:					Yes Yes		] No* ] No*		
5.	Scum collection system working	pro	operly:		[X]	Yes	1	] No*	[	] NA
6.	Sludge collection system working	g p	roperly:		[X]	Yes	[	] No*		
7.	Influent, effluent baffle systems	w	orking proper	ly:	[X]	Yes	[	] No*		
8.	Chemical addition: Chemicals:				[ NA	] Yes	[X	] No		
9.	Effluent characteristics:									
10.	General condition:				[X]	Good Good	[	] Fair	[	] Poor

Comments:

 Some of the crossbars holding up the grates over the tank are rusty and may need to be replaced in the future.

#### **UNIT PROCESS: Ultraviolet (UV) Disinfection**

1.	Number of UV lamps/assemblies:	2	In operation:		1
2.	Type of UV system and design dosage:	Trojan 3000 F	тр		
3.	Proper flow distribution between units:		[ ] Yes	[ ] No*	[X] NA
4.	Method of UV intensity monitoring:		Intensity Me	eters	
5.	Adequate ventilation of ballast control boxes:		[X] Yes	[ ] No*	[ ] NA
6.	Indication of on/off status of all lamps provided:		[X] Yes	[ ] No*	
7.	Lamp assemblies easily removed for maintenance	e:	[X] Yes	[ ] No*	
8.	Records of lamp operating hours and replaceme dates provided:	nt	[X] Yes	[ ] No*	
9.	Routine cleaning system provided: Operate properly: Frequency of routine cleaning:		[X] Yes [X] Yes Weekiy	[ ] No* [ ] No*	
10.	Lamp energy control system operate properly:		[X] Yes	[ ] No*	
11.	Date of last system overhaul:		September 2	2, 2009	
	<ul> <li>a. UV unit completely drained</li> <li>b. all surfaces cleaned</li> <li>c. UV transmissibility checked</li> <li>d. output of selected lamps checked</li> <li>e. output of tested lamps</li> <li>f. total operating hours, oldest lamp/assembly</li> <li>g. number of spare lamps and ballasts available:</li> </ul>		[X] Yes [X] Yes [ ] Yes [ ] Yes NA 42220 2 oth on order	[ ] No* [ ] No* [X] No* [X] No*	1
12.	UV protective eyeglasses provided:		[X] Yes	[ ] No*	
	General condition:		[ ] Good	[X] Fair	[ ] Poor

#### Comments:

- 8. Hours displayed for the system in use- 42220
- 4. Current Intensity display flashing 0.0- Les said they can't get it to work properly- they think there is a short in the wiring somewhere. I explained that the DEQ's policy is that if a system has intensity meters, they must be in good condition and in use. These meters are the only method at this point we have of assuring the system is working.

On 9-17/18-09 I talked to Les and Charlie and was told that an electrician had been out to check the wires -problem is with the sensor itself. They are in the process of ordering new sensor.

Problems with the Intensity Meter were also noted in the Inspection report dated 9/13/2006.

11. UV bulbs are replaced annually and cleaned weekly.

#### **UNIT PROCESS: Post Aeration**

1.	Number of units: 1	In operation:	1		
2.	Proper flow distribution between uni	ts: [ ] Yes [ ] No*	[ <b>X</b> ] NA		
<b>3.</b>	Evidence of following problems: <ul><li>a. dead spots</li><li>b. excessive foam</li><li>c. poor aeration</li><li>d. mechanical equipment failure</li></ul>	[ ] Yes* [ ] Yes* [ ] Yes* [ ] Yes*	[X] No [X] No [X] No [X] No	[ ] NA	
4.	How is the aerator controlled?	[ ] Time clock []	K] Manual	[ ] Continuous	[ ] Other <sup>a</sup>
5.	What is the current operating sched	ule? <b>Continuous</b>			
6.	Step weirs level:	[ ] Yes [ ] No	[ <b>X</b> ] NA		
7.	Effluent D.O. level:	7.6 mg/L @ 21.0 °	C at efflue	ent weir by S. Alle	en at 1302
8.	General condition:	[ <b>X</b> ] Good [ ] Fair	[ ] Poor		
Com	ments:				

pH= 7.15 s.u. @ 20.9 °C at the effluent weir by S. Allen at 1254.

#### **UNIT PROCESS: Flow Measurement**

	[ ] Influe	int [ ] Intermediate	[X] Eπiuent
1.	Type measuring device: Ultr	asonic	
2.	Present reading: 30	99290 (totalizer)	
3.	Bypass channel: Metered:	[ ] Yes [ ] Yes	[ <b>X]</b> No [ ] No [ <b>X</b> ] NA
4.	Return flows discharged upstream Identify:	[ <b>X</b> ] No	
5.	Device operating properly:	[X] Yes	[ ] No*
6.	Date of last calibration: 5-	7-09	
7.	Evidence of following problems:		
	<ul><li>a. obstructions</li><li>b. grease</li></ul>	[ ] Yes* [ ] Yes*	[ <b>X</b> ] No [ <b>X</b> ] No
8.	General condition:	[X] Good	[ ] Fair [ ] Poor

Comments:

#### **VPDES NO VA0089133**

#### **UNIT PROCESS: Effluent/Plant Outfall**

1.	Type Outfall	[X] Shore base	ed	[	] Submerged		
2.	Type if shore based:	[ ] Wingwall		[	] Headwall	[X] Rip Rap	
3.	Flapper valve:	[ ] Yes	[ <b>X</b> ] No	[	] NA		
4.	Erosion of bank:	[ ] Yes	[ <b>X</b> ] No	[	]NA		
5.	Effluent plume visible?	[ ] Yes*	[ <b>X</b> ]No				
6.	Condition of outfall and	supporting str	uctures:	E	] Good	[X] Fair	[ ] Poor*
7.	Final effluent, evidence a. oil sheen b. grease c. sludge bar d. turbid effluent e. visible foam f. unusual color	of following pr [ ] Yes*	oblems: [X] No [X] No [X] No [X] No [X] No [X] No				

#### Comments:

- The plant effluent passes over a weir, enters a pipe which discharges to a grated drain, then through a second pipe to discharge to the environment.
- The rip rap lined channel to the receiving stream mentioned in the previous inspection report was buried and grassy at the time of this inspection. As of Sept 24<sup>th</sup>, operators were going to dig it up and return to original contours.

# Attachment 4

To: Alison Thompson

Rebecca Shoemaker From:

Date: July 13, 2016

Planning Statement for Aldie WWTP Subject:

Permit Number: VA0089133

#### Information for Outfall 001:

Discharge Type:

Municipal

Discharge Flow: Receiving Stream: 0.015 MGD Little River

Latitude / Longitude:

38 58 39 77 38 14

Rivermile:

4.58

Streamcode:

1aLIV

Waterbody:

VAN-A08R

6<sup>th</sup> Order HUC:

PL13

Water Quality Standards: Section 9, Class III, No special standards

Drainage Area:

41.4 square miles

1. Please provide water quality monitoring information for the receiving stream segment. If there is not monitoring information for the receiving stream segment, please provide information on the nearest downstream monitoring station, including how far downstream the monitoring station is from the outfall.

This facility is located on Little River. DEQ Ambient monitoring station 1aLIV004.78 is located on Little River at Route 50, approximately 0.20 mile upstream from Outfall 001. DEQ Ambient monitoring station 1aLIV001.70 is located on Little River at Route 15, approximately 3.0 miles downstream from Outfall 001. The following is the water quality summary for this segment of Little River, as taken from the 2014 Integrated Report:

Class III, Section 9.

DEQ monitoring stations located in this segment of Little River:

- ambient water quality monitoring station 1aLIV001.70, at Route 15
- ambient water quality monitoring station 1aLIV004.78, at Route 50

Biological monitoring finds benthic macroinvertebrate impairments, resulting in an impaired classification for the aquatic life use. A benthic (sediment) TMDL for the Little River watershed has been completed and approved. The recreation and wildlife uses are considered fully supporting. The fish consumption use was not assessed.

2. Does this facility discharge to a stream segment on the 303(d) list? If yes, please fill out Table A.

Yes.

Table A. 303(d) Impairment and TMDL information for the receiving stream segment

Waterbody Name	Impaired Use	Cause	Year first Listed as Impaired	TMDL completed	WLA	Basis for WLA			
Impairment l	Information	in the 2014 Integrated	Report						
Little River	Aquatic Life	Benthic Macroinvertebrates	1998	Goose Creek and Little River Sediment TMDL 4/26/2004	0.7 tons sediment/ year*	TSS concentration 30 mg/L 0.015 MGD			

<sup>\*</sup>This facility was assigned a total WLA of 3.5 tons/year in the Benthic TMDL for the Goose Creek and Little River watersheds. This total WLA was calculated based upon the permitted maximum average concentration for TSS (mg/L) and an assumption of the facility operating at five times the design flow. The factor of five for the design flow was used as a conservative measure to build in future growth in the watershed. Although the future growth for the watershed was determined by the design flow of each facility within in the watershed, the future growth is available for both new and expanding permits in the watershed. The actual WLA for this facility without including the future growth is 0.7 tons/year.

3. Are there any downstream 303(d) listed impairments that are relevant to this discharge? If yes, please fill out Table B.

Yes.

Table B. Information on Downstream 303(d) Impairments and TMDLs

Waterbody Name	Impaired Use	Cause	Year first Listed as Impaired	Distance From Outfall	TMDL completed	WLA	Basis for WLA				
Impairment Information in the 2014 Integrated Report											
Goose Creek Reservoir	Fish Consumption	PCBs	2006	11.3 miles	No						
Goose Creek	Recreation	E. coli	2006	12.3 miles	Goose Creek Watershed Bacteria 05/01/2003	4.16E+10 cfu/year fecal coliform bacteria  2.61E+10 cfu/year E. coli bacteria*	200 cfu/100 ml fecal coliform 126 cfu/100 ml E. coli  0.015 MGD				

<sup>\*</sup> The WLA is expressed in the Goose Creek Watershed Bacteria TMDL as cfu/year fecal coliform bacteria.

4. Is there monitoring or other conditions that Planning/Assessment needs in the permit?

There is a completed downstream TMDL for the aquatic life use impairment for the Chesapeake Bay. However, the Bay TMDL and the WLAs contained within the TMDL are not addressed in this planning statement.

The Goose Creek Reservoir, which is located approximately 11.3 miles downstream from this facility, is listed with a PCB impairment. In support for PCB TMDL development for the Goose Creek Reservoir, this facility is a candidate for low-level PCB monitoring, based upon its designation as a municipal discharger. Low-level PCB analysis uses EPA Method 1668, which is capable of detecting low-level concentrations for all 209 PCB congeners. DEQ staff has concluded that low-level PCB monitoring is not warranted for this facility as it is a small treatment facility that is not expected to be a source of or discharge PCBs. Based upon this information, this facility will not be requested to monitor for low-level PCBs.

5. Fact Sheet Requirements – Please provide information regarding any drinking water intakes located within a 5 mile radius of the discharge point.

There are no public water supply intakes located within five miles of this discharge.

# Attachment 5

# FRESHWATER WATER QUALITY CRITERIA / WASTELOAD ALLOCATION ANALYSIS

Facility Name:

Aldie WWTP

Permit No.: VA0089133

Receiving Stream:

Little River

Version: OWP Guidance Memo 00-2011 (8/24/00)

Stream Information		Stream Flows		Mixing Information		Effluent Information	
Mean Hardness (as CaCO3) =	83.6 mg/L	1Q10 (Annual) =	0.11 MGD	Annual - 1Q10 Mix =	7.01 %	Mean Hardness (as CaCO3) =	50 mg/L
90% Temperature (Annual) =	23.4 deg C	7Q10 (Annual) =	0.14 MGD	- 7Q10 Mix =	100 %	90% Temp (Annual) =	20 deg C
90% Temperature (Wet season) =	12,7 deg C	30Q10 (Annual) =	0,3 MGD	- 30Q10 Mix =	100 %	90% Temp (Wet season) =	15 deg C
90% Maximum pH =	8 SU	1Q10 (Wet season) =	1.2 MGD	Wet Season - 1Q10 Mix =	54.92 %	90% Maximum pH =	7.5 SU
10% Maximum pH =	7 SU	30Q10 (Wet season)	3 MGD	- 30Q10 Mix =	100 %	10% Maximum pH =	SU
Tier Designation (1 or 2) =	1	30Q5 =	0,56 MGD			Discharge Flow =	0.015 MGD
Public Water Supply (PWS) Y/N? =	n	Harmonic Mean =	2.6 MGD			· ·	
Trout Present Y/N? =	n						
Early Life Stages Present Y/N? =	У						

Parameter	Background		Water Qua	lity Criteria			Wasteload	Allocations			Antidegradat	tion Baseline		A	ntidegradatio	on Allocations			Most Limiti	ng Allocation	8
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН
Acenapthene	0			na	9.9E+02			na	3.8E+04		24			_	-	40	220	_	_	na	3.8E+04
Acrolein	0		_	na	9.3E+00		-	na	3.6E+02			46	240	-				_		na	3.6E+02
Acrylonitrile <sup>C</sup>	0			па	2.5E+00		_	na	4.4E+02		_		_	=				_		na	4.4E+02
Aldrin <sup>C</sup> Ammonia-N (mg/l)	0	3.0E+00		na	5.0E-04	4.5E+00	-	па	8.7E-02	144	24			_	-	-	227	4.5E+00	-	na	8.7E-02
(Yearly) Ammonia-N (mg/l)	0	1.66E+01	1.47E+00	na		2.52E+01	3.09E+01	na	-		-		-	(**	200	#2		2.52E+01	3.09E+01	na	
(High Flow)	0	8.74E+00	2.45E+00	na	***	3.93E+02	4.92E+02	па	100	5.554	**		346)			-		3.93E+02	4.92E+02	na	
Anthracene	0	22		na	4.0E+04		122	na	1.5E+06				77.0	- 22	***			_	-	na	1.5E+06
Antimony	0			na	6.4E+02		200	na	2.5E+04		-			**	122			_		na	2.5E+04
Arsenic	0	3.4E+02	1.5E+02	na	225	5.1E+02	1.6E+03	na	566	_						943	40	5.1E+02	1.6E+03	na	he
Barium	0	- #	-	na				na	-					_				_		na	
Benzene <sup>C</sup>	0			na	5.1E+02	_		na	8.9E+04					_						na	8.9E+04
Benzid <b>ine<sup>c</sup></b>	0			na	2.0E-03			na	3.5E-01						-				_	na	3.5E-01
Benzo (a) anthracene <sup>c</sup>	0	22	22	na	1.8E-01		**	na	3.1E+01	(**)	**	**							-	na	3.1E+01
Benzo (b) fluoranthene <sup>c</sup>	0			na	1.8E-01			na .	3.1E+01		-	-	=7.	-				= .		na	3.1E+01
Benzo (k) fluoranthene <sup>c</sup>	0	-		na	1.8E-01			na	3.1E+01					_		-			_	па	3.1E+01
Benzo (a) pyrene <sup>C</sup>	0	==	22	па	1.8E-01			na	3.1E+01					_						na	3.1E+01
Bis2-Chloroethyl Ether C	0	_		na	5.3E+00			na	9.2E+02	_	_	_		122	-				_	na	9.2E+02
Bis2-Chloroisopropyl Ether	.0	-		na	6.5E+04			na	2.5E+06		**	_			-	22.5	227		_	na	2.5E+06
Bis 2-Ethylhexyl Phthalate C	0		-	na	2.2E+01			na	3.8E+03								_		_	па	3.8E+03
Bromoform <sup>C</sup>	0			па	1.4E+03	_		na	2.4E+05			**	-				_				2.4E+05
Butyibenzylphthalate	0			na	1.9E+03			na	7.3E+04	_				140	-	22	22			па	7.3E+04
Cadmium	0	2.3E+00	9.6E-01	na	<u> </u>	3.4E+00	9.9E+00	na			-						_	3.4E+00	9.9E+00	па	
Carbon Tetrachloride <sup>c</sup>	0			na	1.6E+01			na	2.8E+03			-			**	227	-	3.42.700	3.32.700	па	2.8E+03
Chlordane <sup>c</sup>	0	2.4E+00	4.3E-03	na	8.1E-03	3.6E+00	4.4E-02	na	1.4E+00			_		_				3.6E+00	4.4E-02	na 	
Chloride	0	8.6E+05	2.3E+05	na	<u> </u>	1.3E+06	2.4E+06	na				_		_					4.4E-02 2.4E+06	па	1.4E+00
TRC	0	1.9E+01	1.1E+01	па	-	2.9E+01	1.1E+02	na				220				**	**	1.3E+06		na	
Chlorobenzene	0		-	па	1.6E+03	2.52.401	-	na	6.1E+04			_		_				2.9E+01	1.1E+02	na na	6.1E+04

Parameter	Background		Water Qua	lity Criteria		T	Wasteload	I Allocations			Antidegradat	ion Raseline		Δ,	ntideoradati	ion Allocations			Most I Imitis	ng Allocations	
(ug/l unless noted)	Conc.	Acute	1	HH (PWS)	НН	Acute		HH (PWS)	HH	Acute		HH (PWS)	HH	Acute	Chronic	HH (PWS)	HH	Acute	Chronic	HH (PWS)	НН
Chlorodibromomethane <sup>C</sup>	0			na	1.3E+02	7.0010		na	2.3E+04	Houte	O I I O I I	111 (1 110)		Acute	Chilotile	[ [ [ [ [ [ [ [ [ [ [ [ [ [ [ [ [ [ [ [			Cirronic		
Chloroform				па	1.1E+04			na	4.2E+05			525	##./.		V.20	550	-		_	na	2.3E+04
2-Chloronaphthalene	0			na	1.6E+03		-	na	6.1E+04				-			_			-	па	4.2E+05
2-Chlorophenol	0			na	1.5E+02				5.8E+03		••			_		••		*41	_	na	6.1E+04
Chlorpyrtfos	0 1	8.3E-02	4.1E-02			1		na	0.0E*U3	(77)	***								_	na	5.8E+03
Chromium III		3.8E+02	6.2E+01	na	-	1.3E-01	4.2E-01	na	-									1.3E-01	4.2E-01	na	-
Chromium VI	0			na	-	5.8E+02	6.4E+02	na	-					( <del></del> )	**	-	***	5.8E+02	6.4E+02	na	-
	· 1	1.6E+01	1.1E+01	na 4.05.00	-	2.4E+01	1.1E+02	na	0.55	**	***		-					2.4E+01	1.1E+02	па	-
Chromium, Total Chrysene <sup>c</sup>	0	-	-	1.0E+02	-			na				**	22				-		_	na	-
	0		let.	na	1.8E-02		2640	na	3.1E+00	-		-				<del>24</del> )		22	-	па	3.1E+00
Copper	0	8.5E+00	7.4E+00	па	**	1.3E+01	7.7E+01	na	100	100	55	1775	25	-			-	1.3E+01	7.7E+01	na	: <del></del>
Cyanide, Free	0	2.2E+01	5.2E+00	na	1.6E+04	3.3E+01	5.4E+01	na	6.1E+05	-		-		***		2		3.3E+01	5.4E+01	na	6.1E+05
	0	===	100	na	3.1E-03	-	3440	na	5.4E-01	-		-		_	·	***	**	#	-	na	5.4E-01
DDE °	0		-	na	2.2E-03	-	27.2	па	3.8E-01	177	177	===				52	***			na	3.8E-01
DDT <sup>C</sup>	0	1.1E+00	1.0E-03	na	2.2E-03	1.7E+00	1.0E-02	na	3.BE-01	**	-			_			-	1.7E+00	1.0E-02	na	3.8E-01
Demeton	0	***	1.0E-01	na		-	1.0E+00	па	100	••		**	94	-			_	11	1.0E+00	na	
Diazinon	0	1.7E-01	1.7E-01	na		2.6E-01	1.8E+00	na	2.00						44	**		2.6E-01	1.8E+00	na	
Dibenz(a,h)anthracene <sup>C</sup>	0			na	1.8E-01		-	na	3.1E+01				1	_					_	na	3.1E+01
1,2-Dichlorobenzene	0		***	na	1.3E+03		-	na	5.0E+04	**	794	44		_		••	_			na	5.0E+04
1,3-Dichlorobenzene	0			na	9.6E+02		_	na	3.7E+04					-					_	na	3.7E+04
1,4-Dichlorobenzene	0			па	1.9E+02		_	na	7.3E+03	~			=			**	**		_	na	7.3E+03
3,3-Dichlorobenzidine <sup>C</sup>	0			na	2.8E-01		_	na	4.9E+01		-		_	_		_				na	4.9E+01
Dichlorobromomethane <sup>C</sup>	0		-	na	1.7E+02		_	па	3.0E+04	-		***				_	_			na	3.0E+04
1,2-Dichloroethane <sup>c</sup>	0			na	3.7E+02			па	6.5E+04		_		_	_						na	6.5E+04
1,1-Dichloroethylene	0	184	1946	na	7.1E+03			na	2.7E+05	-	-		_	_		=				na	2.7E+05
1,2-trans-dichloroethylene	0			па	1.0E+04			na	3.8E+05			940				_			_		3.8E+05
2,4-Dichlorophenol	0			na	2.9E+02	_		na	1.1E+04		050			_	-	_				na	
2,4-Dichlorophenoxy					2.02.02			THE	1.12.04				=	100		-	_	_		na	1.1E+04
acetic acid (2,4-D)	0	***	**	na	-			па	396		: <del></del>	**		***	**	-		-	-	na	
1,2-Dichloropropane <sup>C</sup>	0		-	na	1.5E+02			па	2.6E+04		-					**	***		-	na	2.6E+04
1,3-Dichloropropene <sup>C</sup>	0	-	**	na	2.1E+02	**		па	3.7E+04	44	-	77.				=			-	na	3.7E+04
Dieldrin <sup>C</sup>	0	2.4E-01	5.6E-02	na	5.4E-04	3.6E-01	5.8E-01	na	9.4E-02	**				-		**		3.6E-01	5.8E-01	na	9.4E-02
Diethyl Phthalate	0			na	4.4E+04			na	1.7E+06	-	-			**	***			-	-	na	1.7E+06
2,4-Dimethylphenol	0	-		na	8.5E+02			na	3.3E+04		**			-	277			_		na	3.3E+04
Dimethyl Phthalate	D			na	1.1E+06			na	4.2E+07			_		-		**				na	4.2E+07
Di-n-Butyl Phthalate	0	0.75	200	na	4.5E+03			па	1.7E+05	***	***	360	**		-					na	1.7E+05
2,4 Dinitrophenol	0			na	5.3E+03		•	na	2.0E+05			-		:25	-	**				na	2.0E+05
2-Methyl-4,6-Dinitrophenol	0			na	2.8E+02		-	na	1.1E+04	-				_		22	22		_	na	1.1E+04
2,4-Dinitrotoluene <sup>C</sup> Dioxin 2,3,7,8-	0	-	-	na	3.4E+01			na	5.9E+03	**		<del>40</del> 5.	·	-		**			-	па	5.9E+03
tetrachlorodibenzo-p-dioxin	0	_		na	5.1E-08			na	2.0E-06	**		_			+	**	**		_	na	2.0E-06
1,2-Diphenylhydrazine <sup>G</sup>	0	200	1940	na	2.0E+00		_	na	3.5E+02		GE	2.0	122	_	_			-	_	na	3.5E+02
Alpha-Endosulfan	0	2.2E-01	5.6E-02	na	8.9E+01	3.3E-01	5.8E-01	na	3.4E+03	-	200	<del></del>		94-	322-1			3.3E-01	5.8E-01		3.4E+03
Beta-Endosulfan	0	2.2E-01	5.6E-02	па	8.9E+01	3.3E-01	5.8E-01	na	3.4E+03					_	**		**	3.3E-01	5.8E-01	na	
Alpha + Beta Endosulfan	0	2.2E-01	5.6E-02	_	-	3.3E-01	5.8E-01		0.42.00	40	***	4	722	_	75E	7.5	- 75	3.3E-01		na	3.4E+03
Endosulfan Sulfate	0			na	B.9E+01		5.0L-01	na	3.4E+03	_		_	_		-	192	22	3.32-01	5.8E-01		2 45.00
Endrin	0	8.6E-02	3.6E-02	na	6.0E-02	1.3E-01	3.7E-01	na	2.3E+00			_			-	-		4.25.04	-	na	3.4E+03
Endrin Aldehyde	0	0.0L-02	3.0L-02		3.0E-01	1.32-01	3.7=-01		1.2E+01		055	=7	y 220	-	_			1.3E-01	3.7E-01	na	2.3E+00
Enalin Aldenyae	V			na	3.UE-UT			na	1.20+01		- 24		-		**					na	1.2E+01

Parameter	Background		Water Qual	litv Criteria		1	Wasteload	l Allocations			Antidegrada	tion Baseline		Δ.	ntideoradatio	on Allocations		1	Most Limiti	ng Allocations	
(ug/i unless noted)	Conc.	Acute	Chronic		НН	Acute		HH (PWS)	НН	Acute	1	HH (PWS)	НН	Acute	1	HH (PWS)	НН	Acute			
Ethylbenzene	0			na	2.1E+03	710010		na	8.1E+04	Piodic	CHICHIC	1111(1440)		Acute	Cilionic	TITTETVO		Acute	Chronic	HH (PWS)	HH
Fluoranthene	0			na	1.4E+02				5.4E+03	_			200		••	-	-	-	-	na	8.1E+04
Fluorene	0				5.3E+03	_		na				-		_				-		na	5.4E+03
Foaming Agents	· 1			na		-		na	2.0E+05	_				••				-	_	na	2.0E+05
Guthion	0	-		na	=	-		na	-	_		**		177	-	••		-	-	na	••
	0		1.0E-02	па		_	1.0E-01	na	22					-				-	1.0E-01	na	
Heptachlor <sup>c</sup>	0	5.2E-01	3.8E-03	na	7.9E-04	7.9E-01	3.9E-02	na	1.4E-01	**	**	***	**	-			-	7.9E-01	3.9E-02	na	1.4E-01
Heptachlor Epoxide <sup>C</sup>	0	5.2E-01	3.8E-03	na	3.9E-04	7.9E-01	3.9E-02	na	6.8E-02				340	340	1.00	-		7.9E-01	3.9E-02	na	6.8E-02
Hexachlorobenzene <sup>C</sup>	0		-	na	2.9E-03	-	-	na	5.1E-01				-	-	075	***		-		na	5.1E-01
Hexachlorobutadiene <sup>C</sup>	0	200	**	na	1.8E+02			na	3.1E+04	***	55	44		_		<b>**</b>	-	2		na	3.1E+04
Hexachlorocyclohexane																					
Alpha-BHC <sup>C</sup>	0		22	na	4.9E-02			na	8.5E+00		***	***	**	-		-		-	-	na	8.5E+00
Hexachlorocyclohexane Beta-BHC <sup>C</sup>					4 == 04																
Hexachlorocyclohexane	0	-	***	na	1.7E-01		-	na	3.0E+01			**	***	-		-				na	3.0E+01
Gamma-BHC <sup>C</sup> (Lindane)	0	9.5E-01	na	na	1.8E+00	1.4E+00		na	3.1E+02									4 45.00			
Hexachiorocyclopentadiene	0			na	1.1E+03	1.42.00					-	(20)	=0		20.00		-	1.4E+00		na	3.1E+02
Hexachloroethane <sup>C</sup>	0		 		3.3E+01		-	na	4.2E+04						-	••		_		na	4.2E+04
	0			na				na	5.8E+03		**	**			**			-	***	na	5.8E+03
Hydrogen Sulfide	, , ,		2.0E+00	na			2.1E+01	na	-		••			-				-	2.1E+01	na	
Indeno (1,2,3-cd) pyrene <sup>c</sup>	0	-		na	1.8E-01		**	na	3.1E+01					022	44			-	***	na	3.1E+01
Iron	0	-		na			**	na	-					(49)	-		**		man	na	-
Isophorone <sup>C</sup>	0	22		na	9.6E+03		-	na	1.7E+06	**	**			-	-	***	<del></del> 0		-	na	1.7E+06
Kepone	0	-	0.0E+00	na	-		0.0E+00	na	-	_	-	200	320	_	_				0.0E+00	па	_
Lead	0	6.4E+01	1.0E+01	na	-	9.7E+01	1.1E+02	na						-	_			9.7E+01	1.1E+02	па	
Malathion	. 0	-	1.0E-01	na			1.0E+00	na	-					5665	:-:	-		**	1.0E+00	na	_
Manganese	0	***	**	na			-	na		_		_		_					_	na	_
Mercury	0	1.4E+00	7.7E-01			2.1E+00	8.0E+00		1	440		-						2.1E+00	8.0E+00		
Methyl Bromide	0		_	na	1.5E+03			na	5.8E+04	_				7.50	-			2.12.00	0.01.00		
Methylene Chloride C	0	22		na	5.9E+03	_		na	1.0E+06			2001		177			-		-	na	5.8E+04
Methoxychlor	0		3.0E-02	na	-		3.1E-01	na	1.0L · 00	1261		-50.			177			=======================================		па	1.0E+06
Mirex	0	222	0.0E+00	na	-	_	0.0E+00					940					-	=	3.1E-01	na	
Nickel	0	1 25+02			4.05.00	4.05.00		na	4.05.05	-				_			-		0.0E+00	na	
		1.2E+02	1.7E+01	na	4.6E+03	1.8E+02	1.7E+02	па	1.8E+05	-		-		1040		55	***	1.8E+02	1.7E+02	na	1.8E+05
Nitrate (as N)	0		**	na		-		na	- 44			440		_			-		-	na	
Nitrobenzene	0			na	6.9E+02	-	-	na	2.6E+04					-	••		-			na	2.6E+04
N-Nitrosodimethylamine <sup>C</sup>	0		-	па	3.0E+01	-	-	na	5.2E+03					***	**	55	55			na	5.2E+03
N-Nitrosodiphenylamine <sup>C</sup>	0	**	-	na	6.0E+01		-	па	1.0E+04	·	-	94.1	22	_		=	=			na	1.0E+04
N-Nitrosodi-n-propylamine <sup>C</sup>	0	-	-	na	5.1E+00	-	~	na	8.9E+02			965	**	( <del>49</del> ):	-		-	**	_	na	8.9E+02
Nonylphenol	0	2.8E+01	6.6E+00	4	**	4.2E+01	6.8E+01	na					-			_		4.2E+01	6.8E+01	na	
Parathion	0	6.5E-02	1.3E-02	na	(44)	9.8E-02	1.3E-01	па	1944	-	222			_	**	22	22	9.8E-02	1.3E-01	na	
PCB Total <sup>C</sup>	0	**	1.4E-02	na	6.4E-04		1.4E-01	na	1.1E-01	**	(**		_	_			22	22	1.4E-01	na	1.1E-01
Pentachlorophenol <sup>c</sup>	0	9.2E-03	1.6E-02	na	3.0E+01	1.4E-02	1.7E-01	na	5.2E+03		-	***				_		1.4E-02	1.7E-01	na	5.2E+03
Phenol	0		-	na	8.6E+05		_	na	3.3E+07			=-	-	527	227		-				
Pyrene	0			na	4.0E+03			na	1.5E+05			_	_	_	100	_	!	_	_	na	3.3E+07
Radionuclides	0	722	722	na	4.02+03			na			-			_				-	-	na	1.5E+05
Gross Alpha Activity	J	_		rid				na		77		ee .	**	_	-			-	-	na	
(pCi/L)	0		••	na			-	na		**				_				_	-	na	
Beta and Photon Activity (mrem/yr)	0			na													100				
Radium 226 + 228 (pCl/L)						-	-	па	-								=			na	
	0		100	na				na	-	-		••	-	-	-			_	-	na	
Uranium (ug/l)	0		••	na	**			na			**				**	••				na	-

Parameter	Background		Water Quality Criteria	ity Criteria			Wasteload A	ad Allocations		A	Antidegradation Baseline	Baseline	_	Anti	Antidegradation Allocations	Allocations			Most Limitir	Most Limiting Allocations	
(ug/l unless noted)	Conc.	Acute	Chronic	Chronic HH (PWS)	王	Acute	Chronic	HH (PWS)	壬	Acute	Chronic HH (PWS)		H	Acute	Chronic H	HH (PWS)	표	Acute	Chronic	HH (PWS)	壬
Selenium, Total Recoverable	0	2.0E+01	5.0E+00	na	4.2E+03	3.0E+01	5.2E+01	na na	1.6E+05	ı	,	:		1			,	3.0E+01	5.2E+01	na	1.6E+05
Silver	0	1.5E+00	ı	na	;	2.3E+00	1	ec	t:	\$)	:	:	,	ı	ı	,	ı	2.3E+00	ı	BU	:
Sulfate	0	:	ı	na	1	ı	ı	na	9	a	1	1	ă	ı	:	:	ı	ı	ı	<u>e</u>	,
1,1,2,2-Tetrachloroethane	0	1	ı	na	4.0E+01	ı	ı	na	7.0E+03	ŀ	:	1	;	ŧ	1	;	,	1	ı	2	7.0E+03
Tetrachloroethylene <sup>c</sup>	0	ī	1:	na	3.3E+01	:	ł	na	5.8E+03	:	1	ı	i	ı	1	ı	į	ı	1	na	5.8E+03
Thallium	0	Î	4	E	4.7E-01	1	;	na	1.8E+01	1	ı		,	1	;	1	1	;	ı	na	1.8E+01
Toluene	0	;	ı	na	6.0E+03	ı	1	na	2.3E+05	*	1		1	1	;	ı	!	ī	ı	na	2.3E+05
Total dissolved solids	0	;	ı	na	:	1	1	па	ı	ŧ	1		į	1	1	;	ı	1	ı	na	ı
Toxaphene <sup>c</sup>	0	7.3E-01	2.0E-04	па	2.8E-03	1.1E+00	2.1E-03	na	4.9E-01	ı		,	1	ı	Ē	ñ	Ē	1.1E+00	2.1E-03	na	4.9E-01
Tributyltin	0	4.6E-01	7.2E-02	na	ı	7.0E-01	7.4E-01	na	1	;	ı	:	:	1	ŀ	:	ı	7.0E-01	7.4E-01	na	:
1,2,4-Trichlorobenzene	0	ì	ı	па	7.0E+01	1	ı	na	2.7E+03	ī	·	:	1	ı	ŀ	ı	:	ı	1	na	2.7E+03
1,1,2-Trichloroethane <sup>C</sup>	0	ł	;	па	1.6E+02	ı	ı	na ,	2.8E+04	ı	I	0		ŧ	#)	1	;	1	1	na	2.BE+04
Trichloroethylene <sup>C</sup>	0	1	:	na	3.0E+02	1	ı	na	5.2E+04	1	:	;	,	ı	į	3	į	.1	ı	na	5.2E+04
2,4,6-Trichlorophenol <sup>c</sup>	0	ī	ı	na	2.4E+01	ı	:	na	4.2E+03	ı	ı	;	-	ı	ı	ı		ı	1	ВП	4.2E+03
2-(2,4,5-Trichlorophenaxy) propionic acid (Silvex)	0	ā	31	па	4	;	ı	na	1	:		;	ı	1	ı	1	ı	1	1	na	,
Vinyl Chloride <sup>G</sup>	0	·	٠	na	2.4E+01	;	ı	na ,	4.2E+03	1	ı	:	1	ı	ı	ı	1	1	1	ВП	4.2E+03
Zinc	0	7.8E+01	9.8E+01	пa	2.6E+04	1.2E+02 1.0E+03	1.0E+03	e L	1.0E+06	ı	1	;	-	;	,	)		4 25403	1 05403	9	4 05406

- 1. All concentrations expressed as micrograms/liter (ug/l), unless noted otherwise
- 2. Discharge flow is highest monthly average or Form 2C maximum for Industries and design flow for Municipals
  - 3. Metals measured as Dissolved, unless specified otherwise
    - 4. "C" indicates a carcinogenic parameter
- 5. Regular WLAs are mass balances (minus background concentration) using the % of stream flow entered above under Mixing Information.
  - Antidegradation WLAs are based upon a complete mix.
- 6. Antideg. Baseline = (0.25(WQC background conc.) + background conc.) for acute and chronic = (0.1(WQC - background conc.) + background conc.) for human health
- Harmonic Mean for Carcinogens. To apply mixing ratios from a model set the stream flow equal to (mixing ratio 1), effluent flow equal to 1 and 100% mix. 7. WLAs established at the following stream flows: 10/10 for Acute, 300/10 for Chronic, Ammonia, 70/10 for Other Chronic, 300/5 for Non-carcinogens and

_	Metal	Target Value (SSTV)	Note: do not use QL's lower than the
	Antimony	2.5E+04	minimum QL's provided in agency
	Arsenic	2.1E+02	guidance
	Barium	na	
	Cadmium	1.4E+00	
	Chromium III	2.3E+02	
	Chromium VI	9.7E+00	
	Copper	5.1E+00	
	lron	na	
_	Lead	3.9E+01	
_	Manganese	na	
	Mercury	8.5E-01	
	Nickel	7.3E+01	
	Selenium	1.2E+01	
	Silver	9.0E-01	
	Zinc	4.7E+01	

# Mixing Zone Predictions for

## Aldie WWTP

Annual

Effluent Flow = .015 MGD Stream 7Q10 = .14 MGD Stream 30Q10 = .3 MGD Stream 1Q10 = .11 MGD Stream slope = .001 ft/ft Stream width = 25 ft Bottom scale = 3 Channel scale = 1

\_\_\_\_\_

### Mixing Zone Predictions @ 7Q10

Depth = .1026 ft Length = 3963.26 ft Velocity = .0934 ft/sec Residence Time = .4909 days

#### Recommendation:

A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.

\_\_\_\_\_

#### Mixing Zone Predictions @ 30Q10

Depth = .1574 ft Length = 2762.33 ft Velocity = .1239 ft/sec Residence Time = .2581 days

#### Recommendation:

A complete mix assumption is appropriate for this situation and the entire 30Q10 may be used.

\_\_\_\_\_\_

#### Mixing Zone Predictions @ 1Q10

Depth = .0902 ft Length = 4407.69 ft Velocity = .0858 ft/sec

Residence Time = 14.2754 hours

#### Recommendation:

A complete mix assumption is appropriate for this situation providing no more than 7.01% of the 1Q10 is used.

Virginia DEQ Mixing Zone Analysis Version 2.1

# Mixing Zone Predictions for Aldie WWTP

Wet Season

Effluent Flow = .015 MGD

Stream 7Q10 = 1.7 MGD Stream 30Q10 = 3.0 MGD

Stream 1Q10 = 1.2 MGD

Stream slope = .001 ft/ft

Stream width = 25 ft

Bottom scale = 3

Channel scale = 1

## Mixing Zone Predictions @ 7Q10

Depth  $= .4391 \, \text{ft}$ 

= 1157.89 ft Length

Velocity = .2418 ft/sec Residence Time = .0554 days

### Recommendation:

A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.

#### Mixing Zone Predictions @ 30Q10

Depth = .6191 ft

Length = 861.92 ftVelocity = .3014 ft/sec

Residence Time = .0331 days

#### Recommendation:

A complete mix assumption is appropriate for this situation and the entire 30Q10 may be used.

### Mixing Zone Predictions @ 1Q10

= .3562 ft Depth

Length = 1384.54 ftVelocity = .2112 ft/sec


Residence Time = 1.8207 hours

#### Recommendation:

A complete mix assumption is appropriate for this situation providing no more than 54.92% of the 1Q10 is used.

Virginia DEQ Mixing Zone Analysis Version 2.1

# Attachment 6



are from the United States Department of the Interior, United States Geological Survey.

Color aerial photography aquired 2002 is from Virginia Base Mapping Program, Virginia Geographic Information Network.

Shaded topographic maps are from TOPO! ©2006 National Geographic http://www.national.geographic.com/topo

All other map products are from the Commonwealth of Virginia Department of Game and Inland Fisheries.

dist=3218 I)

| DGIF | Credits | Disclaimer | Contact shirl.dressler@dgif.virginia.gov | Please view our privacy policy | © 1998-2016 Commonwealth of Virginia Department of Game and Inland Fisheries

# VaFWIS Initial Project Assessment Report Compiled on 6/14/2016, 9:05:06 AM

Help

Known or likely to occur within a 2 mile radius around point 38,58,39.0 77,38,14.0 in 107 Loudoun County, VA

View Map of Site Location

485 Known or Likely Species ordered by Status Concern for Conservation (displaying first 28) (28 species with Status\* or Tier I\*\* or Tier II\*\*)

BOVA Code	Status*	<u>Tier**</u>	Common Name	Scientific Name	Confirmed	Database(s)
060003	FESE	II	Wedgemussel, dwarf	Alasmidonta heterodon		BOVA
050022	FTST		Bat, northern long-eared	Myotis septentrionalis		BOVA
060006	SE	II	Floater, brook	Alasmidonta varicosa		BOVA
050020	SE		Bat, little brown	Myotis lucifugus lucifugus		BOVA
050027	SE		Bat, tri-colored	Perimyotis subflavus		BOVA
030062	ST	I	Turtle, wood	Glyptemys insculpta		BOVA,Habitat
040096	ST	I	Falcon, peregrine	Falco peregrinus		BOVA
040293	ST	I	Shrike, loggerhead	Lanius ludovicianus		BOVA
040379	ST	I	Sparrow, Henslow's	Ammodramus henslowii		BOVA
060081	ST	II	Floater, green	Lasmigona subviridis	Yes	BOVA,TEWaters,Habitat
040292	ST		Shrike, migrant loggerhead	Lanius ludovicianus migrans		BOVA
100248	FS	I	Fritillary, regal	Speyeria idalia idalia		BOVA
040093	FS	II	Eagle, bald	Haliaeetus leucocephalus	:	BOVA
100166	FS	II	Skipper, Dotted	Hesperia attalus slossonae		BOVA
060029	FS	III	Lance, yellow	Elliptio lanceolata	Yes	BOVA,SppObs
030063	CC	III	Turtle, spotted	Clemmys guttata		BOVA
030012	CC	IV	Rattlesnake, timber	Crotalus horridus		BOVA

040372	I	Crossbill, red	Loxia curvirostra		BOVA
040129	I	Sandpiper, upland	Bartramia longicauda		BOVA
040225	I	Sapsucker, yellow-bellied	Sphyrapicus varius		BOVA
040319	I	Warbler, black- throated green	Setophaga virens		BOVA
040306	I	Warbler, golden- winged	Vermivora chrysoptera		BOVA
040052	II	Duck, American black	Anas rubripes		BOVA
040036	II	Night-heron, yellow-crowned	Nyctanassa violacea violacea		BOVA
040213	II	Owl, northern saw-whet	Aegolius acadicus		BOVA
040105	II	Rail, king	Rallus elegans		BOVA
040320	II	Warbler, cerulean	Setophaga cerulea	ž.	BOVA
040266	II	Wren, winter	Troglodytes troglodytes		BOVA

# To view All 485 species View 485

\* FE=Federal Endangered; FT=Federal Threatened; SE=State Endangered; ST=State Threatened; FC=Federal Candidate; FS=Federal Species of Concern; CC=Collection Concern

\*\* I=VA Wildlife Action Plan - Tier I - Critical Conservation Need; II=VA Wildlife Action Plan - Tier II - Very High Conservation Need; III=VA Wildlife Action Plan - Tier III - High Conservation Need; IV=VA Wildlife Action Plan - Tier IV - Moderate Conservation Need

Bat Colonies or Hibernacula: Not Known

#### **Anadromous Fish Use Streams**

N/A

### **Colonial Water Bird Survey**

N/A

Threatened and Endangered Waters (1 Reach)

View Map of All Threatened and Endangered Waters

		T&E Waters Species	
Stream Name	Highest	BOVA Code, Status*, Tier**,	View

	TE*	Common & Scientific Name	Map
Little River (02070008)	ST	060081 ST II Floater, Lasmigona subviridis	Yes

# **Managed Trout Streams**

N/A

**Bald Eagle Concentration Areas and Roosts** 

N/A

**Bald Eagle Nests** 

N/A

Habitat Predicted for Aquatic WAP Tier I & II Species (5 Reaches)

<u>View Map Combined Reaches from Below of Habitat Predicted for WAP Tier I & II Aquatic Species</u>

		•	Ti	er Sp	ecies		
Stream Name	Highest TE*				le, Status <sup>*</sup> , & Scientific	*	View Map
(20700081)	ST	030062	ST	I	Turtle, wood	Glyptemys insculpta	Yes
Howsers Branch	ST	030062	ST	I	Turtle, wood	Glyptemys insculpta	Vac
(20700081)	51	060081	ST	II	Floater, green	Lasmigona subviridis	<u>Yes</u>
Howsers Branch (20700081)	ST	030062	ST	I	Turtle, wood	Glyptemys insculpta	Yes
Little River	ST	030062	ST	I	Turtle, wood	Glyptemys insculpta	Vas
(20700081)	51	060081	ST	II	Floater, green	Lasmigona subviridis	<u>Yes</u>
Little River (20700081)	ST	060081	ST	II	Floater, green	Lasmigona subviridis	Yes

# Habitat Predicted for Terrestrial WAP Tier I & II Species $^{N/A}$

# **Public Holdings:**

# N/A

Compiled on 6/14/2016, 9:05:06 AM 1740205.0 report=TPA searchType= R dist= 3218 poi= 38,58,39.0 77,38,14.0

 $PixelSize=64; Anadromous=0.015455; BECAR=0.013973; Bats=0.010432; Buffer=0.10005; County=0.06658; Impediments=0.022684; Init=0.160678; PublicLands=0.017368; SppObs=0.227542; TEW aters=0.031581; TierReaches=0.071543; TierTerrestrial=0.029882; Total=0.828325; Tracking\_BOVA=0.138741; Trout=0.015868$ 

# Attachment 7

### 9/6/2016 10:55:31 AM

```
Facility = Aldie WWTP
Chemical = Ammonia as N
Chronic averaging period = 30
WLAa = 25.2
WLAc = 30.9
Q.L. = .2
# samples/mo. = 1
# samples/wk. = 1
```

### Summary of Statistics:

```
# observations = 1
Expected Value = 9
Variance = 29.16
C.V. = 0.6
97th percentile daily values = 21.9007
97th percentile 4 day average = 14.9741
97th percentile 30 day average = 10.8544
# < Q.L. = 0
Model used = BPJ Assumptions, type 2 data
```

No Limit is required for this material

The data are:

9

# Attachment 8

#### Public Notice - Environmental Permit

PURPOSE OF NOTICE: To seek public comment on a draft permit from the Department of Environmental Quality that will allow the release of treated wastewater into a water body in Loudoun County, Virginia.

PUBLIC COMMENT PERIOD: XXX, 2016 to XXX, 2016

PERMIT NAME: Virginia Pollutant Discharge Elimination System Permit – Wastewater issued by DEQ, under the authority of the State Water Control Board

APPLICANT NAME, ADDRESS AND PERMIT NUMBER: Loudoun County Sanitation Authority dba Loudoun Water, PO Box 4000, Ashburn, VA 20146, VA0062189

NAME AND ADDRESS OF FACILITY: Aldie WWTP, 39506 John Mosby Hwy, Aldie, VA 20105

PROJECT DESCRIPTION: Loudoun Water has applied for a reissuance of a permit for the public Aldie WWTP. The applicant proposes to release treated sewage wastewaters from residential areas at a rate of 0.015 million gallons per day into a water body. The facility proposes to release the treated sewage wastewaters in the Little River in Loudoun County in the Potomac River watershed. A watershed is the land area drained by a river and its incoming streams. The permit will limit the following pollutants to amounts that protect water quality: pH, BOD<sub>5</sub>, Total Suspended Solids, *E. coli*, and Dissolved Oxygen. The facility shall monitor without limitation the following parameters: Total Nitrogen, Total Kjeldahl Nitrogen, Nitrate+Nitrite, Total Phosphorus, Flow, Influent BOD and Influent TSS.

HOW TO COMMENT AND/OR REQUEST A PUBLIC HEARING: DEQ accepts comments and requests for public hearing by hand-delivery, e-mail or postal mail. All comments and requests must be in writing and be received by DEQ during the comment period. Submittals must include the names, mailing addresses and telephone numbers of the commenter/requester and of all persons represented by the commenter/requester. A request for public hearing must also include: 1) The reason why a public hearing is requested. 2) A brief, informal statement regarding the nature and extent of the interest of the requester or of those represented by the requester, including how and to what extent such interest would be directly and adversely affected by the permit. 3) Specific references, where possible, to terms and conditions of the permit with suggested revisions. A public hearing may be held, including another comment period, if public response is significant, based on individual requests for a public hearing, and there are substantial, disputed issues relevant to the permit.

CONTACT FOR PUBLIC COMMENTS, DOCUMENT REQUESTS AND ADDITIONAL INFORMATION: The public may review the draft permit and application at the DEQ-Northern Regional Office by appointment, or may request electronic copies of the draft permit and fact sheet.

Name: Alison Thompson

Address: DEQ-Northern Regional Office, 13901 Crown Court, Woodbridge, VA 22193

Phone: (703) 583-3834 E-mail: Alison.Thompson@deq.virginia.gov